

H&S

MANURE SPREADERS



GROUND DRIVE MODELS

MODEL 1125 GROUND DRIVE 25 Bu.



6 x 12 Deep Lug traction tires.



The beater on Model 1125 is 20" in diameter and with 8 paddles provides an even spread of material. Shown with optional fine spread pan.



Apron Engage/Disengage Lever

Beater Engage/Disengage Lever

MODEL 1150 GROUND DRIVE 50 Bu.



Deep Lug - 7.60 x 15 traction tires.



The Model 1150 uses a heavy duty 8 paddle beater assembly.



Drive Disengaged



Drive Engaged

MODEL 1180 GROUND DRIVE 80 Bu.



To engage the beater and main apron on Models 1150 and 1180, lower the control lever.



Shown with safety shields removed.

The Beater is chain driven. The main apron is driven by a simple adjustable ratchet drive mechanism.

P.T.O. MODELS

Shown with optional rear trip pan.

The heavy duty 10 paddle beater assembly assures aggressive shredding action with even wide spread patterns.



On all models, the main apron tightener bolts are located outside on the lower right and left corners of the main frame for adjustment.

The large diameter beater on Models 2112 and 2117 provides an even spread pattern.



Shifting on the PTO models is done in the H&S two spread gear box plus beater shutoff.



PTO 80 Bu. **MODEL 2180**



Heavy Duty Steel A-frame and hitch assembly.

PTO 125 Bu. **MODEL 2112**



The H.D. hitch and frame is built to withstand the stress of heavy loads and rough fields.

PTO 175 Bu. **MODEL 2117**



The Model 2117 uses an all welded heavy duty A-frame hitch assembly and full length unitized main frame.

STANDARD FEATURES ON ALL SPREADERS

- Spreader box is constructed of corrosion resistant galvanized steel.
- All spreaders utilize a bonded poly floor to reduce main apron drag and power needed to move the load.

MANURE SPREADER Specifications

MODEL NUMBER	1125 GROUND DRIVE	1150 GROUND DRIVE	1180 GROUND DRIVE	2180 PTO	2112 PTO	2117 PTO
CAPACITY – HEAPED (OLD RATING) BU.	25 BU.	50 BU.	80 BU.	80 BU.	125 BU.	175 BU.
CAPACITY – CU. FT. STRUCK LEVEL	13.6	35	47	53	75	105
TOP OF FLARE WIDTH	28-1/2" (73 cm)	36" (91 cm)	48" (122 cm)	48" (122 cm)	54" (137 cm)	63-1/2" (161 cm)
INSIDE WIDTH	22" (56 cm)	36" (91 cm)	48" (122 cm)	48" (122 cm)	48" (122 cm)	54" (137 cm)
INSIDE LENGTH	6' (183 cm)	8'1" (264 cm)	7'1" (216 cm)	7'4" (223 cm)	10'6" (320 cm)	11'1" (338 cm)
INSIDE DEPTH	17" (43 cm)	17-1/2" (44 cm)	17-1/2" (44 cm)	19-3/4" (50 cm)	22" (56 cm)	25-3/4" (65 cm)
OVERALL LENGTH	9'1" (277 cm)	13'4" (406 cm)	13'4" (406 cm)	13'10" (422 cm)	15'3" (465 cm)	17'8" (538 cm)
OVERALL LOADING HEIGHT – TOP OF FLARE	30" (76 cm)	32-1/2" (82 cm)	33" (84 cm)	35" (89 cm)	43-1/2" (110 cm)	45-1/2" (116 cm)
OVERALL HEIGHT W/HYD. ENDGATE	N/A	N/A	N/A	N/A	N/A	49"
OVERALL WIDTH W/STANDARD TIRES	42" (107 cm)	58" (147 cm)	72" (183 cm)	76" (193 cm)	80" (203 cm)	83-1/2" (212 cm)
STANDARD TIRE SIZE	6.00 X 12	7.60 X 15	7.60 X 15	6.70 X 15	10.00 X 15	10R X 22.5
SPINDLE SIZE	1-1/4" (3 cm)	1-3/4" (4 cm)	2" (5 cm)	2" (5 cm)	2" (5 cm)	2" (5 cm)
DIAMETER OF BEATER	20" (51 cm)	17-1/2" (44 cm)	18-1/2" (47 cm)	18-1/2" (47 cm)	22" (56 cm)	27" (68 cm)
NUMBER OF PADDLES	8	8	10	10	10	8
MAIN APRON CHAIN	55	62	67H	67H	67XH	T-ROD
BOX CONSTRUCTION	CORROSION RESISTANT GALVANIZED STEEL	CORROSION RESISTANT GALVANIZED STEEL	CORROSION RESISTANT GALVANIZED STEEL	CORROSION RESISTANT GALVANIZED STEEL	CORROSION RESISTANT GALVANIZED STEEL	CORROSION RESISTANT GALVANIZED STEEL
FLOOR CONSTRUCTION	BONDED POLY	BONDED POLY	BONDED POLY	BONDED POLY	BONDED POLY	BONDED POLY
APRON DRIVE	ADJUSTABLE RATCHET DRIVE	ADJUSTABLE RATCHET DRIVE	ADJUSTABLE RATCHET DRIVE	GEARBOX, 2 SPEED PTO	GEARBOX, 2 SPEED PTO	GEARBOX, 2 SPEED PTO
UPPER BEATER	N/A	N/A	N/A	N/A	N/A	OPTIONAL
SWING AWAY JACK	N/A	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
WEIGHT W/TIRES	350 LBS. (159 kg)	790 LBS. (358 kg)	975 LBS. (442 kg)	1140 LBS. (517 kg)	1600 LBS. (726 kg)	2030 LBS. (921 kg)
OPTIONS	FINE SPREAD PAN	FINE SPREAD PAN	FINE SPREAD PAN	FINE SPREAD PAN	FINE SPREAD PAN	FINE SPREAD PAN OR HYD. END GATE

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.

Buy the BEST

BUY

H&S



NEED A QR CODE READER? DOWNLOAD THE FREE APP TO YOUR SMARTPHONE!

Models and specifications are subject to change without prior notice.

7/16 4M

H&S MANUFACTURING

2608 S. Hume Avenue
P.O. Box 768 • Telephone (715) 387-3414
FAX (715) 384-5463 • Website www.hsmfgco.com

MARSHFIELD, WI 54449



H&S WAREHOUSE 10145 Lakeshore Road
P.O. Box 1260 • Telephone (716) 736-7595
FAX (716) 736-7596 • Website www.hsmfgco.com

RIPLEY, NY 14775