

H&S

Available with
or without a roof



**"6200
Series"**

Standard 24"
Spring Assist
Extension with
the ability to tilt
DOWNWARD 22
degrees!

NEW FEATURES INCLUDE:

- 5200 & 6200 Series are available in Apron or Twin Auger unload systems
- Faster unload time and the smoothest unloading system on the market
- Spring loaded tighteners on the beater drive chains
- 5200 Series Boxes features a removable roof
- 6219 & 6221 Models feature an optional roof
- Standard 24" spring assist cross conveyor extension has the ability to tip DOWNWARD 22 degrees on the 5200 & 6200 Series
- Hydraulic Cross Conveyor Fold/Unfold is optional on the 5200 & 6200 Series (Standard on the 7200 Series)

NEW Swept-Back"
unit look/design



"5200 Series"

**"HEAVY DUTY
BLACK LINE"**
Forage Boxes
are available in
17' through 27'
Models!



"7200 Series" w/Electric Controls

5200 Series Front Unload Specifications

- ◆ Available in 17', 19' & 21' Models
- ◆ 2.5" x 2.5" Tubular Uprights
- ◆ 5" – 6 Gauge Structural Channel Cross Members
- ◆ 10" – 7 Gauge Channel Main Stringers set on 42" Spacing
- ◆ 2" Main Apron Shaft
- ◆ 667X Main Apron Chain
- ◆ Aluminized Box Sides & Rear
- ◆ Left Hand Discharge
- ◆ Single Lever Variable 12 Speed Unload
- ◆ 3 – 18" 4-Bar Staggered Spiral Beaters
- ◆ 22" Wide Cross-Conveyor w/#550 Chain/Slat
- ◆ 24" Spring Assist Cross-Conveyor Extension
- ◆ Standard Length 540 RPM PTO
- ◆ Removable Roof
- ◆ Highway Lighting & Power Cord
- ◆ Running Gear Hold-Down Kit

- ◆ Inside Width 7' 4-1/4" (88.25)
- ◆ Inside Height 8' 3" (99")
- ◆ Overall Width 9' 4" (112")
- ◆ Overall Height 10' (120")
- ◆ 5217 Overall Lgth. 20' 8" (248")
- ◆ 5219 Overall Lgth. 22' 8" (272")
- ◆ 5221 Overall Lgth. 24' 8" (296")

Cubic Ft. Cap. - No Roof/Struck

- ◆ 5217 = 858.48
- ◆ 5219 = 963.23
- ◆ 5221 = 1,067.98

5200 Options

- ◆ 540 RPM PTO/Long in-lieu-of standard PTO (For use w/Tractor Quick Hitches)
- ◆ Hydraulic Drive Factory Installed in-lieu-of standard PTO - 2000 Series Motor **(1) Remote Needed - Hoses Included**
- ◆ 4th Beater Kit (Dealer installed)
- ◆ Electric Cab Control for Front Unload Speed Adjustment
- ◆ 2' Extension Hydraulic Cylinder Kit **(1) Remote Needed - Hoses Included**
- ◆ No Roof

6200 Series Front & Rear Unload Specifications

- ◆ Available in 19', 21' & 23' Models
- ◆ 2.5" x 2.5" Tubular Uprights
- ◆ 5" – 6 Gauge Structural Channel Cross Members
- ◆ 8" – 7 Gauge Channel Main Stringers set on 34" Spacing
- ◆ 2" Main Apron Shaft
- ◆ 667X Main Apron Chain
- ◆ Aluminized Box Sides & Rear
- ◆ Left Hand Discharge
- ◆ Single Lever Variable 12 Speed Unload
- ◆ 3 – 18" 4-Bar Staggered Spiral Beaters
- ◆ 22" Wide Cross-Conveyor w/#550 Chain/Slat
- ◆ 24" Spring Assist Cross-Conveyor Extension
- ◆ Hydraulic Drive - 2000 Series Motor **(1) Remote Needed - Hoses Included**
- ◆ Automatic Locking/Unlocking Tailgate
- ◆ Hydraulic Gate Delay
- ◆ No Roof
- ◆ Highway Lighting & Power Cord

- ◆ Inside Width 7' 4-1/4" (88.25)
- ◆ Inside Height 7' 2" (86")
- ◆ Overall Width 9' 4" (112")
- ◆ Overall Height 10' 2" (122")
- ◆ 6219 Overall Lgth. 24' 3" (291")
- ◆ 6221 Overall Lgth. 26' 3" (315")
- ◆ 6223 Overall Lgth. 28' 3" (339")

Cubic Ft. Cap. - No Roof/Struck

- ◆ 6219 = 986.30
- ◆ 6221 = 1,091.24
- ◆ 6223 = 1,196.19

6200 Options

- ◆ 540 RPM PTO/Standard Length in-lieu-of Hydraulic Drive
- ◆ 540 RPM PTO/Long in-lieu-of Hydraulic Drive (For use w/Tractor Quick Hitches)
- ◆ 4th Beater Kit (Dealer installed)
- ◆ 2' Extension Hydraulic Cylinder Kit **(1) Remote Needed - Hoses Included**
- ◆ Roof for 19' & 21' Models
- ◆ Electric Cab Control for Front Unload Speed Adjustment
- ◆ Roof Hood for all models
- ◆ 42" Running Gear Conversion Kit

7200 Series Front & Rear Unload Specifications

- ◆ Available in 23', 25' & 27' Models
- ◆ Electric-Over-Hydraulic Drive System (EH) **(1) Remote needed for Front Unload (Hoses Included) or, (1) Remote needed for Rear Unload (Hoses Included)**
- ◆ 2.5" x 2.5" Tubular Uprights
- ◆ 5" – 6 Gauge Structural Channel Cross Members
- ◆ 2" Main Apron Shaft
- ◆ Large Heavy Duty Apron Drive Gearbox
- ◆ 8" – 7 Gauge Channel Main Stringers set on 34" Spacing
- ◆ Poly Style Floor
- ◆ 667XH Main Apron Chain
- ◆ Bolted Aluminized Box Sides & Rear
- ◆ Left Hand Discharge
- ◆ 3 – 18" 4-Bar Staggered Spiral Beaters
- ◆ 22" Wide Cross-Conveyor w/#550 Chain/Slat
- ◆ 24" Hydraulic Fold Cross-Conveyor Extension
- ◆ Automatic Locking/Unlocking Tailgate
- ◆ Hydraulic Gate Delay
- ◆ No Roof
- ◆ Highway Lighting & Power Cord

- ◆ Inside Width 7' 4-1/4" (88.25)
- ◆ Inside Height 7' 2" (86")
- ◆ Overall Width 9' 4" (110")
- ◆ Overall Height 10' 2" (122")
- ◆ 7223 Overall Lgth. 26' 11" (323")
- ◆ 7225 Overall Lgth. 28' 11" (347")
- ◆ 7227 Overall Lgth. 30' 11" (371")

Cubic Ft. Cap. - No Roof/Struck

- ◆ 7223 = 1,196.19
- ◆ 7225 = 1,301.13
- ◆ 7227 = 1,406.08

7200 Options

- ◆ 4th Beater Kit (Dealer installed)
- ◆ Roof Hood for all models
- ◆ 42" Running Gear Conversion Kit



H&S Manufacturing

Ph. #715.387.3414

www.hsmfgco.com

H&S RESERVES THE RIGHT TO CHANGE ITS PRODUCTS OR THE DESCRIPTION AT ANY TIME WITHOUT NOTICE OR OBLIGATION. MODELS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

HSMFG052620