

FEEDER WAGONS & 7+4 FEEDER BOX



H&S HAS A MODEL TO FIT YOUR OPERATION

SLANT BAR FEEDER

Slant bars help prevent cattle from moving in and out. Low, comfortable height of tank sides. All sizes of cattle can feed with heads in unit (except cattle with horns).





H&S MAKES YOUR FEEDING DEPENDABLE & EASIER.

- The main feed pan is constructed of prime steel with the square tubing around the top of the feed pan. Square tubing is 40% stronger than pipe.
- H&S bunks are easy to clean out spoiled feed from the feeder tub. No clutter of numerous pipes or tubes are welded in to clean around.
- H&S bunks feature a **90**° **turing radius** with tricycle front end, 6 hole hubs and wheels, and quick hitch tongue.

MODEL	WEIGHT WITH 9.5L X 15 TIRES
16' SINGLE AXLE	1890 LBS.
20' SINGLE AXLE	2060 LBS.
24' SINGLE AXLE	2520 LBS.
24' TANDEM	2746 LBS.
30' TANDEM	3450 LBS.

STEEL ALL PURPOSE FEEDER WAGONS







FAR SUPERIOR TO ANY SIN SLANT BAR FEEDER EFI

- Chopped green feed.
- Large round and square bales.
- Small round and square bales.
- Silage and Haylage.
- Chopped hay and grou
- 16' unit has 30 feedir





/IILAR FEEDER WAGONFICIENTLY FEEDS

und feed.

ng openings.

- 20' unit has 36 feeding openings.
- 24' unit has 42 feeding openings.
- 30' unit has 50 feeding openings.



have a full axle all the way through the unit.



7+4 FEEDER BOX

*Shown with feeder elevator in the level unloading postion to illustrate reach from side of box.

Available in either front unload or front and rear unload.





Pictured above shows the discharge height in elevated position.

The H&S Feeder Box can be mounted on a 12 ton oscillating tandem trailer with $12.5L \times 15$ tires, truck mounted, or running gear mounted.



CONTROL BOX

The very simple, easy to operate electric-over-hydraulic control box mounts on the tractor or in the truck cab.

MODEL	
POWER	HYDRAULIC DRIVE
HYDRAULIC REQUIREMENTS	(2000 PSI, 10 GPM)
FEEDER APRON DRIVE	WORM GEAR (BRONZE)
SPEEDS	INFINITE VARIABLE
MAIN APRONS	4 CHAINS - 667H PINTLE
BEATERS	2 - 18" DIAMETER, 4 SPIRAL BAR
BEATER DRIVE	#50 ROLLER CHAIN
CROSS CONVEYOR	#550 ROLLER CHAIN OR ANGLE CROSS SLATS
CROSS CONVEYOR DRIVE	SPROCKET AND #50 ROLLER CHAIN
CROSS CONVEYOR WIDTH	22"
DISCHARGE	LEFT SIDE UNLOADING ELEVATOR
DISCHARGE OPENING	533 SQ. IN.
DISCHARGE HEIGHT: MINIMUM (45 DEGREE ANGLE) MAXIMUM (0 DEGREE ANGLE)	33" 39"
INSIDE LENGTH	16'
INSIDE WIDTH	7' - 4"
INSIDE HEIGHT	48"
CAPACITY: BY VOLUME, STRUCK LEVEL BY WEIGHT	454 CU. FT. 20,000 LBS.
OVERALL LENGTH WITH CHASSIS	23' 7"
OVERALL WIDTH: CONVEYOR UP CONVEYOR DOWN	9' - 8" 12' - 4"
OVERALL LOADING HEIGHT WITH CHASSIS	8' - 2"
WEIGHT	5570 LBS.
SIDES	1/2" FIBERGLASS REINFORCED PLYWOOD (FRP)
FLOOR	½" POLY BONDED PLYWOOD
HEIGHT FROM BOTTOM OF FRAME TO TOP OF BOX	69"
RECOMMENDED TRUCK CAB TO CENTER OF AXLE MINIMUM	150"

STANDARD EQUIPMENT: emergency stop mechanism, highway light package, electronic controls

STRONG HERITAGE STRONG PEOPLE STRONGER FUTURE!

For over 50 years, H&S Manufacturing has made life better. Our team is committed to building long-lasting relationships and high performance machinery. As we continue to grow and move forward we want you to farm smarter with our most reliable and innovative farming equipment.

H&S is proud to be American Made!

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.









Models and specifications are subject to change without prior notice.

10/18 3M

H&S MANUFACTURING

2608 S. Hume Avenue
Telephone (715) 387-3414

FAX (715) 384-5463 • Website www.hsmfgco.com
MARSHFIELD, WI 54449

