



9215 HI-DUMP Box

"High Capacity" and "Gentle Handling"



FEATURES:

- Combination 10 and 12 gauge steel tub construction.
- Heavy gusseted and reinforced box style frame.
- With a GVWR rating of approximately 45,000 lbs., and an empty box weight of around 15,000 lbs., the 9215 is capable of lifting and dumping approximately 30,000 lbs of product to meet the GVWR capacity.
- The variable dumping height gives you more versatility at harvest time.
- ENTIRE dumping cycle should take approximately two minutes depending on hydraulic supply output.
- The master/slave hydraulic system automatically rephases at the end of each cylinder stroke and has the flexibility to top off a truckload with a partial dump – not restricted to a full dump cycle.
- Right hand dump has a 47 degree dumping angle.
- (2) 27" x 16" Sight windows and (2) tub access panels.
- Standard highway lighting.
- Adjustable height single clevis swivel hitch.
- Telescoping/adjustable length hitch pole.
- Rear Tow Bar

OPTIONS:

- 18" Dumping Lip Extension
- Dual Weight Box Package
- Safety Chain

Models & Specifications are subject to change without prior notice.

HDB9215 Specifications



Cubic Ft. Capacity Struck Level w/o Ext.	863
Cubic Ft. Capacity Struck Level w/ Ext.	1,129
Inside Length of Box	180" (15')
Inside Width of Box - Bottom/Top	65"/136" (5' 5"/11' 4")
Depth of Box	89" (7' 5")
Overall Length Min./Max w/ Pole Adjustment	304"/328" (25' 4"/27' 4")
Overall Width	158" (13' 2")
Shipping Width (top slide to hub cap)	143" (11' 1")
Loading Height	130" (10' 10")
Shipping Height	117" (9' 9")
Front Lift Cylinder (size/length)	5.5" x 72"
Rear Lift Cylinder (size/length)	4.75" x 72"
Dump Cylinders (size/length)	5" x 71.25"
Maximum Dump Lip Clearance	31" (2' 7")
Minimum Dump Height	116" (9' 8")
Maximum Dump Height	184" (15' 4")
Maximum Ground Clearance	15" (1' 3")
Tread Width	121" (10' 1")
Spindle Size	4.5"
Tire	30.5 x 32 R1 16 Ply Radial Tires
Jack	12,000 lbs.
Shipping Weight w/ Tires	15,243 lbs.



H&S Manufacturing Co., Inc.

Ph. #715.387.3414

www.hsmfgco.com

HSMFG100920