

FAST | EFFICIENT | RELIABLE

UF6136 ULTRA-FLEX MERGER



H&S



Triple-head merger with 36' of continuous working width and three 12' heads

FEATURES

- 1. ISOBUS ready with Aux-N capabilities
- 2. Most head travel in its class, ideal for merging uneven terrains.
- 3. Patented center cam/center drive design provides smooth, clump-free windrows — **NO BUNCHING!**
- 4. **WIDEST** cross-conveyor belt in its class at 42"
- 5. Softest merger head footprint in the industry.
- 6. Dual drive cross conveyors
- 7. Self-contained hydraulic system features a 65-gallon reservoir, no tractor remotes are needed!
- 8. High torque rated hydraulic motors for the heads and cross conveyor are the largest in the industry, and coupled with heavy 2-ply cross-conveyor belts, are able to handle heavy crops.
- 9. Electric over hydraulic logic (manual overrides) defaults belts to the right.
- 10. Rubber mounted teeth
- 11. Hydraulic steerable rear axle (patent pending)
- 12. 2-point hitch



STANDING OUT FROM THE COMPETITION

What sets the **ULTRA-FLEX** apart from the competition is the capacity it can handle. This merger is designed to handle extreme conditions. It's ideal for the custom operator or large dairy farm making 35' triple-mower cuts in extreme terrain that needs to move a lot of material in a short amount of time.

Note: UF6136 Model Year 2024 is a limited release.

ULTRA-FLEX MERGER

Smooth, clump-free windrows



OPTIONS



In-Cab Display



ADDITIONAL FEATURES

The patented **SOFT-SHOE™** suspension system wears the field as little as possible and extends skid shoe life. Float pressure is adjustable from the operator seat on the fly. The heavy-duty 385/65 x 22.5 radial tires don't scuff in the field!

UF6136 SPECIFICATIONS

WORKING WIDTH	36'
TRANSPORT WIDTH	12'
TRANSPORT LENGTH	24'
TRANSPORT HEIGHT	11' 10"
PICK-UP HEADS	3 (12')
HEAD TRAVEL	20" LEFT AND RIGHT / 16" CENTER
PICK-UP STRIPPERS	POLY
PICK-UP TEETH	RUBBER MOUNTED
CROSS CONVEYOR BELT WIDTH	42"
CROSS CONVEYOR ON/OFF/RIGHT/LEFT/SPLIT	ELECTRIC-OVER-HYDRAULIC (ADJUSTABLE IN-CAB)
SKID SHOE HEIGHT	HYDRAULIC (ADJUSTABLE IN-CAB)
HEAD SUSPENSION	EXCLUSIVE SOFT-SHOE™ SUSPENSION TECHNOLOGY SYSTEM
DRIVE SYSTEM	HYDRAULIC
PTO	1 3/8" OR 1 3/4 1000 RPM STD
OIL RESERVOIR CAPACITY	65 GAL
HYDRAULIC REQUIREMENTS - STANDARD UNIT	NO HYDRAULIC REQUIREMENT FROM THE TRACTOR
TIRE SIZE	385/65 X 22.5 RADIAL TIRES
TRACTOR REQUIREMENTS	150 HP



STRONG HERITAGE

STRONG PEOPLE

STRONGER FUTURE!



WARRANTY: See operator's manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.

1/24

H&S Manufacturing Company, Inc.

www.hsmfgco.com



H&S MAIN OFFICE • 2608 S. HUME AVE.
MARSHFIELD, WI 54449 • (715) 387-3414



H&S WAREHOUSE • 10145 LAKESHORE ROAD
P.O. BOX 1260 • RIPLEY, NY 14775 • (716) 736-7595